NC

INSTALLATION AND OPERATION GUIDE FOR
HARGROVE VENTED GAS LOGS

Double Stack and Triple Stack Burners with RMBE Millivolt Valve (2B), RME Millivolt Valve (2A), or NO VALVE (0A)

NATIONAL FIREPLACE INSTITUTE NFI CERTIFIED www.nficertified.org

We recommend that our gas hearth products be installed and serviced by professionals who are certified in the U.S. by the National Fireplace Institute® (NFI) as NFI Gas Specialists.

Vented Decorative Appliance for Installation in Solid-Fuel Burning Fireplaces.

Installation and service must be provided by a qualified installer, service agency or the gas supplier.

NOTE: ADEQUATE FIREPLACE VENTILATION IS REQUIRED FOR SAFETY.
READ INSTRUCTIONS FULLY BEFORE INSTALLING OR OPERATING.
INSTALLER: LEAVE THIS MANUAL WITH THE APPLIANCE.
CONSUMER: RETAIN THIS MANUAL FOR FUTURE REFERENCE.

WARNING:

If the information in this manual is not followed exactly, a fire or explosion may result, causing property damage, personal injury, or loss of life.

WHAT TO DO IF YOU SMELL GAS

1. **Open a window.**
2. **Do not try to light any appliance.**
3. **Do not touch any electrical switch; do not use the phone in your building.**
4. **Immediately call your gas supplier from a neighbor's phone. Follow the gas supplier's instructions.**
5. **If you cannot reach your gas supplier, call the fire department.**

FOR YOUR SAFETY

Do not store or use gasoline or other flammable vapors and liquids in the vicinity of this or any other appliance.

IMPORTANT: Installation and service must be performed by a qualified professional installer, service agency, or the gas supplier.

NOTE: This appliance is only for use with the type of gas indicated on the rating plate.

Solid fuels shall not be burned in a fireplace where a decorative appliance is installed.

This Hargrove vented gas log set is to be installed only in a solid-fuel burning fireplace with a working flue and constructed of noncombustible material. The installation, including provisions for combustion and ventilation air must conform to the *National Fuel Gas Code, ANSI Z223.1/NFPA 54, or the CSA B149.1, Natural Gas and Propane Installation Code*, and applicable local building code. A damper clamp is included to maintain the minimum permanent vent opening and to prevent full closure of the damper blade. The gas log set must be burned with the **damper completely open (In the Commonwealth of Massachusetts the damper must either be welded in the fully open position or completely removed)** and the chimney free of any obstructions or restrictions.

The realistic yellow flame produces carbon monoxide and soot. Under normal conditions, these products are exhausted up the chimney. If fumes or soot, from the gas burning, are evident in the room when the damper is fully open it indicates that the fireplace draft is defective. Do not operate your gas log set until the fireplace draft is corrected. **It is the homeowners responsibility to assure their fireplace has adequate draft.**

IMPORTANT PRE-INSTALLATION AND FIREPLACE SAFETY INFORMATION

WARNING: This appliance assembly contains burner orifices specifically for the input gas and Btu rating. Modifying or failure to use the factory orifice may cause property damage, personal injury or loss of life.

1. It is recommended that adults be present when this gas appliance is operating. It is recommended that this unit is not left burning when unattended or while anyone is sleeping.

2. Do not use a natural gas set for propane or a propane set for natural gas. If the gas type is not correct. DO NOT INSTALL. Contact your dealer for immediate assistance.

3. There are many different local codes for gas fire logs. The installation and the provision for combustion and ventilation air must conform to local codes and, or in the absence of local codes, with the National Fuel Gas Code ANSI Z223.1 – (most current revision).

4. Gas log sets must be installed by personnel qualified for installing gas appliances.

5. This appliance must be installed only in a solid-fuel burning fireplace with a working flue and constructed of noncombustible materials. Solid fuels are not to be burned in a fireplace where a decorative appliance has been installed.

6. A permanent free opening must be provided by either the fireplace chimney or chimney damper to vent flue gasses. Any chimney damper must be fixed in a manner, which will maintain the permanent free opening at all times. Use Table II to determine the minimum permanent free opening based on chimney height and the appliance Btu input rating. Refer to the Damper Stop section for additional directions.

7. The minimum free opening is based only on two factors; chimney height and Btu input rating. Many other factors affect the fireplace drafting. It is the homeowner's responsibility to assure their fireplace has adequate draft. If fumes or soot from the gas burning are evident in the room when the damper is fully open, it indicates that the fireplace draft is defective. Do not operate your gas log set until the fireplace draft is corrected. Consult your fireplace specialist.

8. A fireplace screen must be in place when the appliance is operating and, unless other provisions for combustion air are provided, the screen shall have an opening(s) for introduction of combustion air.

9. When glass fireplace doors are used, always operate gas log set with the doors fully open to allow for proper combustion air and to keep control valves from overheating.

10. The minimum inlet supply pressure for input adjustment is 5.0 inches (natural gas) 11 inches (propane gas) in water column. The maximum inlet supply pressure is 10.5 inches (natural gas) 13 inches (propane gas) in water column.

11. The appliance and its individual shut-off valve must be disconnected from the gas supply piping system during any pressure testing of that system at test pressures more than 1/2 psig (3.5kPa). The appliance must be isolated from the gas supply piping system by closing its individual manual valve during pressure testing equal to or less than 1/2 psig (3.5kPa).

12. The fireplace chimney or venting system should be examined annually and cleaned as required by a qualified agency.

13. After burning for several hours, the logs become fragile and should not be handled. Knocking or rubbing logs can cause concrete to crumble and is not covered under the warranty.

14. To clean the logs, use a soft dry paintbrush for periodic dusting of the gas fire logs.

15. To clean the burner, shut off the gas supply, remove the burner pan media, and vacuum the burner ports. After cleaning, replace burner pan media and light the pilot according to the lighting instructions.

SPECIFICATIONS AND DIMENSIONS



Minimum Fireplace Dimensions
With Valve

SET SIZE	FRONT WIDTH	REAR WIDTH*	Double/Triple DEPTH	Double/Triple HEIGHT
18”	24”	24”	15” / 25”	18” / 23”
24”	30”	30”	15” / 25”	18” / 23”
30”	36”	36”	15” / 25”	18” / 23”
36”	42”	42”	15” / 25”	18” / 23”
48”	54”	54”	21” / 31”	18” / 23”
60”	66”	66”	21” / 31”	18” / 23”

Minimum Fireplace Dimensions
NO VALVE

SET SIZE	FRONT WIDTH	REAR WIDTH*	Double/Triple DEPTH	Double/Triple HEIGHT
18”	22”	18”	15” / 25”	18” / 23”
24”	28”	24”	15” / 25”	18” / 23”
30”	34”	30”	15” / 25”	18” / 23”
36”	40”	34”	15” / 25”	18” / 23”
48”	52”	48”	21” / 31”	18” / 23”
60”	64”	60”	21” / 31”	18” / 23”

BTU CHART

SET SIZE	DOUBLE STACK	+	TRIPLE STACK	=	TOTAL BTU
18”	70,000		60,000		130,000
24”	90,000		80,000		170,000
30”	110,000		90,000		200,000
36”	130,000		100,000		230,000
48”	170,000		110,000		280,000
60”	200,000		120,000		320,000

PRE-INSTALLATION CHECKLIST

FIREPLACE AND CHIMNEY

- Fireplace is approved for solid-fuel burning and made of non-combustible materials.
- Operational damper with a chimney free of any obstruction or restriction.
- Fireplace has proper draft to accommodate decorative appliance.
- Fireplace is free from debris or ash.
- Fireplace is free of obstruction such as log grate, log lighter, etc.; that would prohibit the installation of the log set.
- If the floor is recessed or glass doors are installed on the fireplace, the appliance may need to be elevated to ensure proper air flow.
- Consult table to determine if the set is properly sized for the installation in the fireplace.

GAS LINE

- Ensure gas line is in safe condition and that it is adequate for the installation.
- Check gas line sizing to ensure it is properly sized for the appliance.
- For ease of installation gas line should be located on the right side of the fireplace when possible.
- Turn the gas supply line off and you are ready to begin burner installation.

DAMPER STOP INSTALLATION

Attach the damper stop clamp to the fireplace damper blade. Position the clamp to prevent full closure of the fireplace damper blade.

If the damper stop provided does not fit, the installer shall install a permanent damper stop that will keep the damper open to a minimum opening as determined on page 3 Table II of the instructions.



CAUTION
THE DAMPER MUST BE FULLY OPEN WHEN OPERATING THE GAS LOGS!

IMPORTANT: In the Commonwealth of Massachusetts the damper must be either permanently welded in the fully open position or completely removed.

BURNER PARTS LIST
(DOUBLE STACK NO VALVE)



*Photos not to scale

ITEM	PART NUMBER	DESCRIPTION
1	DG	Double Stack Burner
2	SD-10 / VM	Sand (NG) / Vermiculite (LP)
3	RW	Rockwool
4	VC	Volcanic Cinder
5	1AC-18	Aluminum connector
6	FCNW-18	Non-Whistling Flex Connector
7	DS	Damper Stop
8	CAP-12	3/4” Burner Cap
9	CAP-8	1/2” Burner Cap
10	50-6-8	Brass Elbow 1/2” FIP x 3/8” FL
11	50-8-8	Brass Elbow 1/2” FIP x 1/2” FL
12	49-8-12	Brass Elbow 3/4” MIP x 1/2” FL
13	PRB-12-8	Pipe Bushing 3/4” x 1/2”
14	T-12	Pipe-T 3/4”
15	49-6-8	Brass Elbow 3/8” MIP x 1/2” FL

NOTE: Replacement parts can be ordered from your local Hargrove dealer.

BURNER PARTS LIST
(DOUBLE STACK and TRIPLE STACK NO VALVE)



*Photos not to scale

ITEM	PART NUMBER	DESCRIPTION
1	DG	Double Stack Burner
2	BB	Triple Stack Burner
3	SD-10 / VM	Sand (NG) / Vermiculite (LP)
4	RW	Rockwool
5	VC	Volcanic Cinder
6	1AC-18	Aluminum connector
7	FCNW-18	Non-Whistling Flex Connector
8	DS	Damper Stop
9	CAP-12	3/4” Burner Cap
10	CAP-8	1/2” Burner Cap
11	50-6-8	Brass Elbow 1/2” FIP x 3/8” FL
12	50-8-8	Brass Elbow 1/2” FIP x 1/2” FL
13	49-6-8	Brass Elbow 1/2” MIP x 3/8” FL
14	PRB-12-8	Pipe Bushing 3/4” x 1/2”
15	T-12	Pipe-T 3/4”
16	T-8	Pipe-T 1/2”
17	N-8x3.5	1/2” x 3.5” Nipple
18	EL-12-8	Reduce Elbow 3/4” x 1/2”
19	49-8-12	Brass Elbow 3/4” MIP x 1/2” FL

NOTE: Replacement parts can be ordered from your local Hargrove dealer.

BURNER PARTS LIST
(DOUBLE STACK 2B)



ITEM	PART NUMBER	DESCRIPTION
1	DG	Double Stack Burner
2	SD-10 / VM	Sand (NG) / Vermiculite (LP)
3	RW	Rockwool
4	VC	Volcanic Cinder
5	1AC-18	Aluminum connector
6	FCNW-18	Non-Whistling Flex Connector
7	DS	Damper Stop
8	CAP-12	3/4” Burner Cap
9	CAP-8	1/2” Burner Cap
10	50-6-8	Brass Elbow 1/2” FIP x 3/8” FL
11	50-8-8	Brass Elbow 1/2” FIP x 1/2” FL
12	49-8-12	Brass Elbow 3/4” MIP x 1/2” FL
13	PRB-12-8	Pipe Bushing 3/4” x 1/2”
14	T-12	Pipe-T 3/4”
15	N-12x3	Pipe Nipple 3/4” x 8”
16	SE-12	Street Elbow 3/4”
17	RSTPGNG-18	Pilot Assembly (NG)
	RSTPG-18LP	Pilot Assembly (LP)
18	RSBMV-C	High Capacity Millivolt Valve
19	AM-55	Brass Air Mixer
20	49-6-8	Brass Elbow 1/2” MIP x 3/8” FL
21	N-8x1	Nipple 1/2” x 1” long
22	AM-56	Brass Air Mixer

*Photos not to scale

BURNER PARTS LIST
(DOUBLE STACK 2B and TRIPLE STACK 2A)



ITEM	PART NUMBER	DESCRIPTION
1	DG	Double Stack Burner
2	BB	Triple Stack Burner
3	RSBMV-C	High Capacity Millivolt Valve
4	RSMVNG-C	Millivolt Valve
5	RSTPGNG-18	Pilot Assembly (NG)
	RSTPG-18LP	Pilot Assembly (LP)
6	SD (NG) / VM (LP)	Sand (NG) / Vermiculite (LP)
7	RW	Rockwool
8	VC	Volcanic Cinder
9	FCNW-22-8	1/2” Flex Connector
10	FCNW-18	Non-whistling Flex Connector
11	DS	Damper Stop
12	CAP-12	3/4” Burner Cap
13	CAP-8	1/2” Burner Cap
14	50-6-8	Brass Elbow 1/2” FIP x 3/8” FL
15	50-8-8	Brass Elbow 1/2” FIP x 1/2” FL

BURNER PARTS LIST CONT'D
(DOUBLE STACK 2B and TRIPLE STACK 2A)

ITEM	PART NUMBER	DESCRIPTION
16	49-8-12	Brass Elbow 3/4" MIP x 1/2" FL
17	PRB-12-8	Pipe Bushing 3/4" x 1/2"
18	T-12	Pipe-T 3/4"
19	N-12x3	Pipe Nipple 3/4" x 8"
20	SE-12	Street Elbow 3/4"
22	49-6-8	Brass Elbow 1/2" MIP x 3/8" FL
23	EL-12-8	Reduce Elbow 3/4" x 1/2"
24	N-8x3.5	1/2" x 3.5" Nipple
25	T-8	1/2 Black Pipe T
26	N-8x8	1/2" x 8" Nipple
27	EL-8-6	Reduce Elbow 1/2" x 3/8"
28	N-6x1.5	3/8" x 1 1/2"" Nipple

NOTE: Replacement parts can be ordered from your local Hargrove dealer.

BURNER AND GRATE POSITIONING

Check that the gas is turned off.
Center the burner on the fireplace floor. The burner should be located under the flue opening.

The grate should be placed over the burner so the front legs of the grate are just in front of the burner pipe. Once the final positioning is established, mark the burner and grate position on the floor of the fireplace for reference points.

Remove the grate and proceed with the gas connection.

NOTE: If the floor is recessed or glass doors are installed, burner must be elevated with firebrick or equivalent to ensure proper air flow over valve systems.

BURNER POSITION

GAS CONNECTION

Check that the gas is turned off.

Any remote kits should be installed on the burner at this point, refer to instructions with kit for that installation.

The gas supply line should be ½" inside diameter (ID) up to 30 feet and ¾" for longer distance.

Use the non-whistling flex connector provided in the accessory kit to connect the gas supply to the burner kit. Check to make sure the burner is in the correct position.

Turn the gas supply on and check connection for leaks using a soapy solution.

NOTE: At this point install and program any remote kits, refer to the instructions provided with those kits for installation.

IMPORTANT: The minimum inlet supply pressure for the purpose of input adjustment is 5.0 inches (natural gas) 11 inches (propane gas) in water column.
The maximum inlet supply pressure is 10.5 inches (natural gas) 13 inches (propane gas) in water column.

2B DS

2B DS / 2A TS



NO VALVE DS



NO VALVE TS



LIGHTING THE PILOT (2A)

Read the lighting instruction plate attached to the gas valve or located at the end of these instructions.

Push in gas control knob slightly and turn clockwise until the knob will not turn any longer. This is the “OFF” position. The word off should be at the 12 o’clock position on the control knob.

Slightly push in on pilot knob and turn valve to the “PILOT” position. Push the knob in all the way and hold in. Immediately light the pilot. *(The pilot is located on the back right corner of the burner pan*) Continue to hold the knob for at least 30 seconds after the pilot is lit. Release the knob and the pilot should remain lit.

Turn the burner to the “ON”, the pilot flame should ignite the main burner within 4 seconds.

Carefully check the connections for leaks using a soapy solution.

NOTE: If the pilot will not stay lit after several tries turn the control off and call a technician.





IMPORTANT: These controls are factory preset and will not normally require additional adjustment of the pilot flame. If field adjustment of the pilot flame is required, adjust using the pilot adjustment screw. The 90 degree pilot should produce 2 flames about 1-1 ½” in 2 directions. One flame should come towards the front of the firebox to ignite the burner and the other, wrapping around the thermocouple to ensure proper valve operation.

WIRING SCHEMATIC (2A)

*If installing a remote control, thermostat, or timer, attach the leads from the optional item to the same terminals as the switch on the Millivolt Valve.

BURNER MEDIA

Fill the burner pan with sand(NG) or vermiculite(LP). The media level should be sloped evenly with the sides of the burner pan. Under filling will cause uneven flame.

Glowing Embers (Rockwool) are placed over the media. For best results pinch off pieces of the rockwool the size of a dime and feather it out

Test fire the burner once again for flame distribution, media can be altered to achieve desired flame appearance.



WIRING SCHEMATIC (2B)



*If installing a remote control, thermostat, or timer, attach the leads from the optional item to the same terminals as the switch on the Millivolt Valve.

LOG INSTALLATION

Install the logs based on the installation diagram provided with the logs set, as stated in step 7, for Radiant Heat logs it will be necessary to remove the grate and install the radiant heat bracket (packaged with Radiant Heat logs) onto the back of the burner pan.

Once the logs have all been place you can readjust the grate positioning to get desired flame pattern. When adjusting grate position be careful as the **GRATE WILL BE HOT**, it might be necessary to let it cool between adjustments.

RECOMMENDED BURN-IN PERIOD: Hargrove gas logs are made of special refractory materials, which withstand high temperatures. One characteristic of this material is retention of moisture. For this reason, we recommend burning the logs for only fifteen minutes during the first burning. After allowing the logs to cool for at least one hour, the set can be burned for any length of time.

LIMITED LIFETIME WARRANTY: Hargrove gas logs carry a limited lifetime warranty against breakage in the original fireplace. Warranty does not include labor. This warranty is void if excessive handling after burning causes breakage. All accessories and metal parts carry a two year limited warranty in the original fireplace. Items will be replaced during this period for the cost of shipping.

VOLCANIC CINDER PLACEMENT

The black volcanic cinders are used to cover the fireplace floor, fittings and tubing around the burner system. Although not functional, the back cinders act as a picture frame to show off the glowing embers and yellow flame.

FOR YOUR SAFETY: Do not use this appliance if any part has been underwater. Immediately call a qualified service technician to inspect the appliance and to replace any part of the system or gas control, which has been underwater

FOR YOUR SAFETY READ BEFORE LIGHTING

WARNING: If you do not follow these instructions exactly, a fire or explosion may result causing property damage, personal injury or loss of life.

A. This appliance has a pilot, which must be lit by hand. When lighting the pilot, follow these instructions exactly.

B. **BEFORE LIGHTING** smell all around the appliance area for gas. Be sure to smell next to the floor because some gas is heavier than air and will settle on the floor.

WHAT TO DO IF YOU SMELL GAS:

1. Do not try to light any appliance.
2. Do not touch any electric switch; do not use any phone in your building.
3. Immediately call your gas supplier from a neighbor's phone. Follow the gas supplier's instructions.
4. If you cannot reach your gas supplier, call the fire department

C. Use only your hand to push in or turn the gas control knob. Never use tools. If the knob will not push in or turn by hand, do not try to repair it. Call a qualified service technician.

D. Do not use this appliance if any part has been under water. Immediately call a qualified service technician to inspect the appliance and to replace any part of the control system and any gas control, which has been underwater

LIGHTING INSTRUCTIONS

1. STOP! Read the safety information above on this label.
2. Push in gas control knob slightly and turn clockwise to **"OFF".**



NOTE: Knob cannot be turned from "PILOT" to "OFF" unless knob is pushed in slightly. Do not force.

3. Wait five (5) minutes to clear out any gas. If you then smell gas, STOP! Follow "B" in the safety information above. If you don't smell gas, go to next step.
4. Find pilot – follow metal tube from the gas control behind the burner pan.



5. Turn knob on gas control counterclockwise to **"PILOT"**.
6. Push in control knob all the way and hold in. Immediately light the pilot with a match. Continue to hold the control knob in for about one minute after the pilot is lit. Release knob and it will pop back up. Pilot should remain lit. If it goes out, repeat steps 3 – 7.

- If knob does not pop up when released, stop and immediately call your service technician or gas supplier.
- If the pilot will not stay lit after several tries, turn the gas control knob to **"OFF"** and call your service technician or gas supplier.

7. Turn gas control knob counterclockwise to **"ON"**.

LIGHTING INSTRUCTIONS

1. Turn knob clockwise from **"ON"** position to the **"PILOT"** position. Push in the gas control knob slightly and turn clockwise to **"OFF"**. Do not force knob.

LIMITED WARRANTY

Refractory and Ceramic Fiber Logs

Hargrove gas logs carry a limited lifetime warranty against any manufactured defect or breakage. This warranty does not cover breakage caused by excessive handling once installed and fired. Contact Customer Service for warranty claim details.

Burner & Grate

If the burner or grate fails due to deterioration within five (5) years of the verified purchase date, contact Customer Service for warranty claim details.

Valves, Remote Controls, & Switching Devices

All valves, remote controls and switching devices are warranted against manufacturing defects which appear within two (2) years of the verified purchase date. Warranty does not cover products that have been damaged by misuse from overheating. Before any product is returned a Return Goods Authorization number (RGA) must be issued by the Customer Service Department. All returns must be accompanied by an explanation of the problem and all necessary parts.

All Other Parts

If any assembled part should fail to operate or be found defective which appear within two years of the verified purchase date, contact Customer Service for warranty claim details

Buyer shall notify Customer Service of any defect covered by this warranty no later than thirty (30) days after defect is discovered. Failure to provide notice within thirty (30) days shall void the limited warranty.

WHAT IS NOT COVERED

1. Removal and reinstallation costs.
2. Labor costs for replacement or repairs.
3. Transportation or shipping cost.
4. The cost of a service call to diagnose trouble.
5. Painted Surfaces.
6. Damage or defect caused by improper installation, accident, misuse, abuse, alteration, or authorized service technician.
7. Replacement of burner or combustion chamber resulting from improper storage of the appliance.

LIMITATIONS AND EXCLUSIONS

1. No one has authority to add to or vary this limited warranty, or to create for Hargrove Manufacturing Corporation any other obligation or liability in connection with this appliance.
2. Any implied warranty applicable to this appliance is limited in duration to the same period of time as this written warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitations may not apply to you.
3. HARGROVE MANUFACTURING CORPORATION WILL NOT BE LIABLE FOR INCIDENTAL, CONSEQUENTIAL, SPECIAL OR CONTINGENT DAMAGES YOU MIGHT SUFFER AS A RESULT OF A CLAIM UNDER THIS WRITTEN WARRANTY OR ANY IMPLIED WARRANTY. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusion may not apply to you.
4. This warranty applies only to the original purchaser and may not be transferred or assigned.
5. If you cannot verity the purchase date of the appliance, the warranty period will begin on the date of which the appliance was manufactured.
6. Replacement or repair parts are warranted for the remaining period of the original part warranty. Warranty parts must be obtained through authorized dealers of this product who will provide original factory replacement parts. Failure to use original factory replacement parts voids this warranty.
7. The maximum liability of Hargrove Mfg. Corp. in connection with this limited warranty shall not in any case exceed the contract price paid for the product claimed to be defective or unsuitable.
8. Purchaser or user agrees to hold Hargrove Mfg. Corp. harmless from all claims by the buyer because of injury or damage to an ultimate user or other person caused by the product sold herein by the seller to the buyer, whether the injury or damage results from the assembly, installation, operation, shipment, storage, or manufacture of this product. Hargrove Mfg. Corp. makes no warranties, expressed or implied, other than those expressly stated herein.

YOUR DUTIES

This appliance must be installed by a qualified installer, operated and maintained in accordance with all applicable codes and the instructions furnished with the appliance. You must provide a receipt verifying the purchase date of the appliance when making a warranty claim with the dealer from which the appliance was purchased.

This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

CONTACT INFO: Hargrove Gas Logs
Wellston Park Rd. – Sand Springs, OK 74063
Toll Free – (800)725-4166
www.hargrovegaslogs.com

Customer Service hours: 8:00am to 4:00pm CST